

TREVIM Hi Performance



PAPERS

you can trust

ESPECIFICACIONES TÉCNICAS

Propiedad	Referencia Estándar	Unidad	Valor Nominal								
Gramaje	ISO 536	g/m ²	135	150	170	190	225	250	300	350	
Rigidez Taber	DL	ISO 2493	mN.m	1.0	1.8	2.0	3.0	4.5	5.0	7.0	11.5
	DT			0.5	0.9	1.0	1.5	2.2	2.5	3.2	5.5
Espesor	ISO 534	μm	155	175	200	220	260	290	335	385	
Lisura Bekk	ISO 5627	s	35	27	23	23	23	23	23	23	
Humedad	ISO 287	%	7.5	7.5	7.5	7.5	7.5	7.5	7.5	7.5	
Blancura CIE	ISO 11475	%	163	163	163	163	163	163	163	163	

DL-Dirección Longitudinal (Sentido de Fibra); DT-Dirección Transversal (Contra Fibra)


Certified for
HP Indigo

Producto certificado por el Rochester Institute of Technology (RIT) para prensas digitales HP Indigo

Certificaciones del producto disponibles



EU Ecolabel: PT/011/003



www.papeldoprado.com

Los valores están sujetos a cambio sin aviso previo.
Última actualización: 07/2024